



THIS RANGE MUST BE CONNECTED WITH CABLE OF 75°C RATING MINIMUM
 WARNING: THIS RANGE MUST BE EARTHED

DANGER 240V
 DISCONNECT POWER BEFORE
 SERVICING UNIT

INSTALLATION INSPECTOR PLEASE NOTE:
 THIS PRODUCT HAS PASSED THE INSULATION RESISTANCE TEST AFTER MANUFACTURE. IF THE RESISTANCE READING IS LOW AT INSTALLATION, IT IS PROBABLY CAUSED BY MOISTURE FROM THE ATMOSPHERE BEING ABSORBED BY THE ELEMENTS AFTER THE RANGE HAS BEEN PRODUCED. (PASS AT 0.01 MΩ AS/NZS 3000 WIRING RULES CLAUSE 8.3.6.2).

0165-003-234
 ECN 12A118A

WARNING
 IT IS ILLEGAL FOR PERSONS OTHER THAN LICENSED ELECTRICAL MECHANICS OR PERSONS AUTHORIZED BY LEGISLATION TO WORK ON THE FIXED WIRING OF ANY ELECTRICAL INSTALLATION. PENALTIES FOR CONVICTION ARE SEVERE.

IMPORTANT SAFETY NOTICE
 This diagram has been prepared for use by electrically qualified service technicians. Electrolux cannot be held responsible for the interpretation of its service publications nor for any injury or damage that may occur in connection with their use.