

TECHNICAL DATE

ZCC5069

PNC no. 943 265 140

TECHNICAL FEATURES

Free standing

Class 1

Hob	Cooker lid Pan support Front right Back right Front left Back left	Enamelled Enamelled Rapid Auxiliary Semi -rapid Semi -rapid		
			2,40 kW 0,90 kW 1,80 kW 1,80 kW	
Oven	Oven Oven burner power Grill Grill burner power Light in the oven Cleaning		Electric 1,70 kW Electric 1,80 kW Lamp 15W type E14 catalyse	
Supply	Rated voltage Rated frequency		230 V 50 Hz	
Accessories	Oven grid Roasting tray Protective screen		Chromed Enamelled	
Dimensions	Height to the hob Width Depth		875 mm 500 mm 600 mm	

SPECIFICATION NOZZLES

Table no.1

Burner	Normal power (kW)	Economic power (kW)	By-pass (mm)	Gas Type	Pressure (mbar)	Nozzle diameter (mm)	Cons	
							m ³ /h	g/h
Rapid	2,40	0,72	0,42	Nat.Gas G13	13	1,24	0,240	-
				Nat.Gas G20	20	1,11	0,240	-
				LPG G30	30	0,80	-	188,4
Semi-rapid	1,80	0,43	0,32	Nat.Gas G13	13	1,11	0,180	-
				Nat.Gas G20	20	0,96	0,180	-
				LPG G30	30	0,71	-	141,3
Auxiliary	0,90	0,35	0,29	Nat.Gas G13	13	0,82	0,090	-
				Nat.Gas G20	20	0,70	0,090	-
				LPG G30	30	0,50	-	70,6

DT000429