

TECHNICAL DATE

ZCG5500
PNC no. 943 264 358

TECHNICAL FEATURES

Free standing

Class 1

Hob	Cooker lid Pan support Front right Back right Front left Back left	Enamelled Enamelled Auxiliary Rapid Rapid Semi -rapid	0,90 kW 2,40 kW 2,40 kW 1,80 kW
Oven	Oven Oven burner power Grill Grill burner power Light in the oven Cleaning	Gas 2,45 kW Gas 1,95 kW Lamp 15W type E14 manual	
Supply	Rated voltage Rated frequency		230 V 50 Hz
Accessories	Oven grid Roasting tray Grill Deflector Turn spit		Chromed Enamelled
Dimensions	Height to the hob Width Depth		850 mm 550 mm 550 mm

SPECIFICATION NOZZLES

Table no.1

Burner	Normal power (kW)	Economic power (kW)	By-pass (mm)	Gas Type	Pressure (mbar)	Nozzle diameter (mm)	Cons	
							m ³ /h	g/h
Rapid	2,40	0,72	0,42	Nat.Gas G13	13	1,24	0,240	-
				Nat.Gas G20	20	1,11	0,240	-
				LPG G30	30	0,80	-	188,4
Semi-rapid	1,80	0,43	0,32	Nat.Gas G13	13	1,11	0,180	-
				Nat.Gas G20	20	0,96	0,180	-
				LPG G30	30	0,71	-	141,3
Auxiliary	0,90	0,35	0,29	Nat.Gas G13	13	0,82	0,090	-
				Nat.Gas G20	20	0,70	0,090	-
				LPG G30	30	0,50	-	70,6
Oven	2,45	1,00	0,46	Nat.Gas G13	13	1,35	0,245	-
				Nat.Gas G20	20	1,20	0,245	-
				LPG G30	30	0,80	-	192,3
Grill	1,95	-	-	Nat.Gas G13	13	1,20	0,195	-
				Nat.Gas G20	20	1,05	0,195	-
				LPG G30	30	0,75	-	150,0

DT000438