



- Q1 = opener left
- Q2 = closer left
- Q3 = closer right
- m1 = fan hot air
- m2 = fan cooling
- m3 = transformer halogen lamp
- m5 = fan cooling magnetron
- m6 = motor stirrer
- m8 = transformer high voltage
- r14 = grill
- r16 = rear
- f1 = oven thermostat
- f2 = safety temp. limiter oven
- f7 = sensor to magnetron
- h4.1 = lamp halogen
- G5 = magnetron
- c2 = interference filter

PE ○ ————

Q1,Q2,Q3: switch position when door closed

1		A		First Edition		S.Grazioli		15.05.06	
POS	ZUST	MODIFICATIONS				SIGNATURE	REQUEST	DATE	
MATERIAL		Leitungsmaterial in Silikon Temp. best. min 180°C Insulation of the cord is silicon, temperature-resistance: min 180°C				MODEL		SCALE	
DESIGN		OWNER		DRN		CHD		DATE	
SC		S.Grazioli		APPR		05.12.05		REPLACES NO DERIVED FROM NO 315 5660 00	
TREATMENT		WEIGHT		TITLE		SCHEMATIC		EUROPEAN METHOD	
				Schaltplan Modul MWO II		schematic MWO II		⚡	
NUMBER		315 5660 12		SHEET		01(01)		REV	
								A	

