

This drawing contains confidential information and is the property of Electrolux, without whose permission it may not be copied, shown or handed to a third party or otherwise used and it is to be returned promptly upon request to the design owner, who is responsible for the drawing.

Items shown in this drawing must not contain substances that are banned according to Directive, 2002/95/EC, the RoHS Directive (Lead, Cadmium, Mercury, hexavalent Chromium, PBB and PBDE), or substances classified as "Banned" or "Restricted" according to the Electrolux Restricted Materials List.

GENERAL TOLERANCES
ANGLES
LENGTHS AND DIAMETERS


Kabelbäume / cable harnesses

Pos.	ELUX No.:	powerboard	group connectors	Anschluss / connection
01	315 7507 00	APD 1ST IN	1 2	br X1/L, X1/3 vio N1/Phase BR4
02	315 7433 01	APD 1ST OUT	1 2	sw f2.1 ws N1/BL4
03	315 7352 02	Heater Main	1 2 3 4 5 6	gr r16 sw r7 ws f2.2 rt r8 br r14
04	315 7434 02	Small Loads N1/BL1	1 2 3 4 5 6 7	bl m1/1 ws A1/1 vio m2/2 gr m2/3 or h4/N (pos04) or m1/2 (pos07)
05	387 2605 02	power supply lightbar platine	1 2 3	vio X1/L, X1/3 ws X1/N, X1/5
06	330 6940 00	User Interface N1/BC1	□□ □□ □□	□□ N3/BI3
07	330 7046 00	meat probe N1/BM1	□□ □□	rt b3/A ws b3/B
08	387 1222 00	connection DS for Light switches N1/BD1	□□ □□ □□	x x Door switch for light
09	387 2552 00	lightbar platine BR01	□□ □□ □□	lightbar left lightbar right
10	387 2586 00	lightbar platine BR02	□□ □□ □□	N3 / BI 5
11	387 2606 00	connection user interface touch input left	□□ □□ □□	foil conductor / Folienleiter user interface left
12	387 2606 00	touch input right	□□ □□ □□	user interface right


Einzellitzen / single wires

Pos.	Kontaktfolge / contact	Auflösung / structure explanation	Farbe / colour	min. \varnothing	
01	m1/2 - h4/L - A1/2 - m2/1 - A2/2	184-400-195-500-195-300-195-300-194	or	0,75	o94
02	f2.1* - r7 - r14 - r16 - r8*	▶ 194-150-195-100-195-150-195-350-194 ▶	sw sw sw sw	1,0-1,0-1,0-1,0	o95
03	PE/1b - BR14	184-260-194 ▶	gng	1,0	143
04	h4/PE - (r7+r14)PE - PE/1b	194-250-195-120-194	gng	1,0	o01
05	X1/N - BR13	194-250-194	bl	1,0	o96
06	X1/N - f2.2	194-550-194	bl	0,75	o05
07	BR7 - BF3	▶ 194-100-194	bl	1,0	126
08	A2/1 - A1/1	194 - 520 - 194	ws	0,75	120
09					
10					
11	Kanban order from factory				
12	f3.1/170° - BF1	cable harness 315 8654 00	or		
13	f3.1/170° - r5	cable harness 315 8654 00	or		
14	r5 - f3.2/120° - h9/1	cable harness 315 8654 00	ws		
15	f3.2/120° - h9/2 - r7	cable harness 315 8654 00	sw		
16	r5 - PE/1b	cable harness 315 8654 00	gng		
17					

connection temperatur sensor



connection temperatur sensor steam



Kanban order from factory

Kontaktfolge/contact	Farbe colour
PE1/1b - h4.1/PE	gng
h4/N - h4.1/N	bl
h4/L - h4.1/L	or

part number: 315 8651 01

Bezeichnung	designation	Elux Sachnummer / Elux part no.
* ▶ Isolierhülse	insulation housing	
Liste Anschlagteile	list of crimp contacts	330 1766 00
Betriebsmittelliste	list of components	330 2222 00
Liste Einzellitzen	list of single wires	315 6867 00
Leitungsmaterial	material of wire	330 5273 00
Zeichnung OVC	drawing OVC	330 6807 00

B change cable harness in Pos. 08 from old 315 1222 00 in 387 1222 00		Büschke	DGT 53771	2007-08-13
A First edition		Büschke	DGT 53292	2007-07-19
POS.	MODIFICATIONS	SIGNATURE	REQUEST	DATE
MATERIAL	MODEL	SCALE	EUROPEAN METHOD	
TREATMENT	WEIGHT	DESIGN USERS	REPLACES	
DESIGN OWNER	pd_high end oven	CHD Büschke	DERIVED FROM	
DGT	DATE 2007-07-19	APPR Büschke	SUPPLY SPECIFICATIONS	
TITLE		wiring built-in oven		
NUMBER		Verdrahtung Einbau-Bratofen		
		315 8879		
		REV	B	
		1/1		

OVC 2000, hot air, L-channel, non pyro, lamp on side, DS for light, meat probe,

VARIANT NUMBER	REPLACED NUMBER	POS.	CHANGES FROM THE BASE NUMBER