

This drawing contains confidential information and is the property of Electrolux, without whose permission it may not be copied, shown or handed to a third party or otherwise used and it is to be returned promptly upon request to the design owner, who is responsible for the drawing.

Items shown in this drawing must not contain substances that are banned according to Directive, 2002/95/EC, the RoHS Directive (Lead, Cadmium, Mercury, hexavalent Chromium, PBB and PBDE), or substances classified as "Banned" or "Restricted" according to the Electrolux Restricted Materials List.

GENERAL TOLERANCES
ANGLES
LENGTHS AND DIAMETERS

Anzahl der Steckmöglichkeiten / Quantity			10					4		2	2	2	2
Steckanschlüsse Quick-Connect terminals													
Anschlußbezeichnung / marking of connector			1 - 2 - 3 - 4 - 5					6	7	8	9	10	11
Schalterstellung Drehwinkel rechtsdrehend Clockwise	0	0	0°										
	1	Lamp	40.0°						X	X	X		
	2	MULTI	80.0°			X	X		X	X	X	X	
	3	INFRA	120.0°	X		X			X	X	X	X	
	4	GRILL 1	160.0°			X			X	X	X	X	
	5	GRILL 2	200.0°	X		X			X	X	X	X	
	6	T/B	240.0°	X	X				X	X	X	X	
	7	BUTTOM	280.0°		X				X	X	X	X	
	8	DEFROST	320.0°					X		X	X		
Anschlußbezeichnung / marking of connector			1a	2a	3a	4a	5a	6a	7a	8a-9a	10a-11a		
Steckanschlüsse Quick-Connect terminals													
Anzahl der Steckmöglichkeiten / Quantity			1	1	1	1	2	1	2	2			

Der Kontakt 2.Schaltstellung 5-5a und 3. Schaltstellung 6-6a müssen jeweils schon geöffnet sein bevor der andere Kontakt schliesst. (Verriegelung)

A First edition				Renner	DGT37038	2005-12-19
POS.	MODIFICATIONS			SIGNATURE	REQUEST	DATE
MATERIAL			MODEL		SCALE	
TREATMENT			DESIGN USERS		REPLACES	
DESIGN OWNER			WEIGHT		DERIVED FROM	
DGT			TITLE		EUROPEAN METHOD	
DATE 2005-12-19			function selector / rotary switch		11 HE / XXX	
APPR Renner			NUMBER		REV	
CHD Hoffmann			387 2529		A	
2D ONLY x					1/1	
CONCEPT 3D -						
EXACT 3D -						

Electrolux